

XCEED®

**Thin, Strong Nitrile Exam Glove with
ERGOFORM™ Ergonomic Design
Technology**

Ergonomically designed to reduce hand fatigue

ERGOFORM™ Technology:

XCEED gloves are designed with proprietary ergonomic design technology to support musculoskeletal health and increase worker productivity

Exceptional tactile sensitivity:

These lightweight, yet strong, nitrile gloves offer a thin design for enhanced tactile sensitivity

Strong barrier integrity: With a low 0.65 AQL, these gloves offer advanced barrier integrity

Strong formulation: XCEED gloves are designed to prevent rips and tears

Reduced waste: Gloves are smartly packaged, with 250 gloves* per box and easy, single glove dispensing to reduce waste

*230 gloves per box for size XL



Industries

- Automotive Aftermarket
- Food Processing
- Life Sciences
- Healthcare
- Agriculture
- Emergency Medical Services
- Utilities
- Warehousing

Recommended For

- General Purpose Auto Aftermarket
- Plant disinfection and sanitization
- All food processing, applications that have food contact
- Assembly of parts
- Sample taking and processing
- Raw material sample collection
- Enhanced tactile sensitivity and dexterity, especially for delicate procedures
- Extra comfort during long, sustained procedures
- Extra comfort during long, sustained procedures
- Protection from Type IV chemical allergies in HCW's or patients
- Standard, moderate risk examination procedures

TECHNICAL DATA SHEET

	Product Information
External Glove Surface	Textured Fingers
Audit Standards	EN ISO 13485:2012
Packaging Overview	250 gloves per dispenser 10 dispensers per case 2500 gloves per case *230 gloves per dispenser (Size XL) *2300 gloves per case (Size XL)
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Malaysia
Product Segmentation	High Touch
Antistatic	Yes

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	240 / 9.5		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	0.65 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.07 / 2.8		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.11 / 4.3		ASTM D3767,EN 420
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	≥ 33	≥ 29	ASTM D412 & D573
Elongation at Break (%)	≥ 500	≥ 400	ASTM D412
Force at break (N)	≥ 7	≥ 7	EN 455-2

ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	7462M1	7462M2	7462M3	7462M4	7462M5

Performance Standards and Regulatory Compliance

