



Nitrile

## Specially designed to protect while minimizing skin irritation

- Manufactured without chemical accelerators for low dermatitis potential and prevention of Type IV skin allergies
- Thin and lightweight construction for tactile sensitivity
- Textured on the fingertips for secure handling of tools and materials



### Industries

- Life Sciences
- Healthcare

### Recommended For

- Assembly of parts
- Sample taking and processing
- Protection from latex Type I allergy and minimize chemical Type IV allergies in HCW's or patients
- Standard patient examinations
- Helping protect skin from drying or cracking
- Protection from Type I latex allergy in HCW's or patients



## TECHNICAL DATA SHEET

### PRODUCT INFORMATION

	Sensation® N73
Material	Nitrile
Color	Blue
Glove Design	Chlorinated, Powder-Free, Silicone Free, Textured Fingers
Cuff	Beaded
Manufacturing/QMS Audit Standards	ISO 13485:2003
Regulatory	ASTM D6319, EN 420:2003 + A1:2009, FDA21 CFR 177-2600-US Food Contact Approved, Food Type: Rubber, US QSR/FDA 510(k) Medical Examination Grade
Packaging	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin	Malaysia
User Needs Segment	High Touch
Available sizes	XS (5.5 - 6), S (6.5 - 7), M (7.5 - 8), L (8.5 - 9), XL (9.5 - 10)
Anti-static	Yes

### PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	240 / 9.5		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.06 / 2.4		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.10 / 3.9		ASTM D3767,EN 420
	<b>BEFORE AGING</b>		<b>AFTER AGING</b>
Ultimate Tensile Strength (MPa)	29	20	ASTM D412 & D573
Elongation at Break (%)	≥ 500	≥ 400	ASTM D3767

### ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	N730	N731	N732	N733	N734

### Performance Standards and Regulatory Compliance

